# **TOSHIBA**





## **6527**AC/7527AC

#### MAIN SPECIFICATIONS

Copy System Indirect Electrostatic Photographic/OPC/Laser Printing/Heat Roller Fusing

10.1\* Color WSVGA Touch Screen Tilting Display Color: 65/75 PPM (LT), Monochrome: 75/85 PPM (LT) Color: 6.4/5.4, Monochrome: 4.5/4.1 Seconds Copy Speed First Copy Out Warm-Up Time From Powering On: Approx. 20 Seconds From Sleep & Low Power: Less Than 15.4 Seconds

**Copy Resolution** 600 x 600 dni

Stack Feed Bypass 3.9" x 5.8" to 12" x 18", 12" x 47" Banner, Envelope

Up to 999 Copies Multiple Copying

Four Drawer Version: Standard 2,280 Sheets/Max. 6,780 Sheets Paper Capacity Tandem Drawer Version: Standard 3,520 Sheets/Max. 8,020 Sheets 300-Sheet DSDF with Double Feed Detection

**Original Feed** 

Max. Original Size LD/A3

**Paper Weights** 

Drawers: 540 Sheets-ST-R to 12" x 18" Paper Feed Sizes Integral Tandem LCF: 1,160 x 2 LT Only

Stack Feed Bypass: 120 Sheets-3.9" x 5.8" to 13" x 19", 12" x 47" Banner

Opt. 2,500-Sheet External LCF LT Only
Opt. 2,000-Sheet Piggyback External LCF LT Only
Drawers: Standard: 540 Sheets x 4-16lb Bond-110lb Cover

Tandem LCF 1,160 Sheets x 2-16lb Bond-110lb Cover

Plus 540 Sheets x 2-16lb Bond-110lb Cover Stack Feed Bypass: 120 Sheets-16lb Bond-110lb Cover Opt. 2,500-Sheet External LCF LT Only-16lb Bond-110lb Cover

Opt. 2,000-Sheet Piggyback External LCF LT Only-16lb Bond-110lb Cover

Standard Automatic Duplex Unit (16lb Bond-140lb Index) Duplex

Reproduction Ratio 25% to 400% 540K/600K Month (Color: 100%) Max Duty Cycle

Approx.470lb 37.6" (W) x 27.5" (D) x 48.3" (H) Weight

Approx. Dimensions

**CMYK Toner Yield** CMY: 39,200, K: 106,600 @ 5% **Power Source** 120 Volts, 50/60 Hz, 16 Amps **Power Consumption** Maximum 2.0kW/2.4kW (120V)

NFMA 5-20 Plug Type Memory

Hard Disk Drive 128GB Solid State Drive (SSD)

#### Security Features

User Authentication, Trusted Platform Module, On-Board Data Scramble Function, SCEP, Disable, e-Filing, Disable Copy, Disk Overwrite\*, IP Address Filtering (10 Sets), MAC Address Filtering (10 Sets), Network Service Control, Network Port Control, SMB Packet Signing, SSL/TLS (HTTP, IPP, LDAP, SMTP, POP, FTP, DPWS, SYSLOG), IPsec (IKEv1, IKEv2), Security Mode Change, CC Certified (ISO/IEC15408)\* with HCD-PP v1.0, IEEE802.1X (Wired/Wireless), Digital Signature for Client Utilities, Password Policy, Password Lock, Password Expiration, Self Testing, Job Access Control, Log Access Control for Job Log, Security Stamp, Role Based Access Control, Secure PDF, Digital Signature for Firmware Update, Integrity Check Function, Image Log, Card Authentication, Biometric Authentication \*Conformance with HCD-PPv1.0 in High Security Mode

**Environmental Standards** 

Certifications

Compatibility

ENERGY STAR® (V3.1), EPEAT Gold, Californian Proposition 65 WHQL (Windows® 8, 8.1, 10, 11, 2012, 2012 R2, 2016/19/22), Novell®, Citrix®, SAP, AirPrint® and Mopria®

#### **SCAN SPECIFICATIONS**

DSDF Scan: Up to 240 IPM Duplex, 120 IPM Simplex Scan Speed

(Monochrome or Color)

Scan Weights 9.3-110lb Bond

RADF Scan: Simplex: 9.3-41.8lb Bond, Duplex: 13.3-41.8lb Bond Scan Modes Standard: Full Color, Auto Color, Monochrome, Grayscale

DOC/XLS/PPT/PDF Scan Resolution

600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi Monochrome: TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, File Formats

Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX Color/Grayscale: JPEG, TIFF-Multi/Single Page, PDF-Multi/Single Page, PDF/A, Slim PDF, Searchable PDF, XPS-Multi/Single Page, DOCX, XLSX, PPTX

**Image Compression** Color/Grayscale: JPEG (High, Middle, Low)

#### e-BRIDGE NEXT PRINT SPECIFICATIONS

PCL5e, PCL5c, PCL6 (PCL XL), PS3, PDF, XPS, JPEG PDL

**Print Resolution** 600 x 600 dpi, 1,200 x 1,200 dpi or

3,600 (Equivalence) x 1,200 dpi (BW/with Smoothing) (PS3 Only) Windows® 8.1,10, 11, Windows Server® 2012/R2, Windows Server® 2016/19/22, Macintosh® (macOS X 10.10-15, 12), Unix®, Linux® Operating Systems

**Network Protocols** TCP/IP (IPv4, IPv6), NetBIOS over TCP/IP, IPX/SPX® for Novell®

Environments, EtherTalk for Macintosh Environments SMB V1-3, LPR/LPD, IPP V1.2 w/Authentication (TLS 1.2/1.3), AppleTalk  $^{8}$ **Printing Protocols** PAP or EtherTalk, Port 9100 (Bi-Directional), NetWare P-SERVER LPD

w/iPrint, Bluetooth (HCRP/BIP/OPP/FTP), WS Print, FTP Windows® 8.1 (32-bit, 64-bit), Windows Server® 2012/R2 (64-bit), Windows Server® 2016/19/22, Windows® 10, 11 (64-bit),

macOS X 10.12-15, 11, 12 RJ-45 Ethernet (10/100/1000 Base-T), USB 2.0 (High-Speed)

Optional IEEE802.11b/g/n, Wireless LAN, Optional Bluetooth AirPrint®, Mopria®, e-BRIDGE Print & Capture Application on iOS and Wireless Device

Android (Available via Apple® App Store or Google Play)

**Device Management** TopAccess Account Control

**Print Drivers** 

Interface

Up to 10,000 Users or 1,000 Departments Supports User Authentication (on Device), Login Name/Password (via Windows® Domain) or Login

Name/Password (via LDAP Server) for Copy, Print, Scan, Fax, List, and User Function

**Accessibility Features** Tilt Front Panel, Job Programs, Universal Grip for Paper Trays, Disable Screen Timeout, Audible Beeps, Optional Voice Assist

**FACSIMILE SPECIFICATIONS** 

Data Compression MH/MR/MMR/JBIG Transmission Speed Approx. 3 Seconds Per Page Fax Modem Speed Up to 33.6 Kbps 100 Jobs (with HDD), 2,000 Destinations Max. 400 Destinations/Job Memory Transmission

Super G3

Scan Speed 0.7 Seconds Per Page, Maximum 73 IPM

#### e-FILING SPECIFICATIONS

Operation Method Color Touch Screen Control Panel or Client PC **Number of Boxes** 1 Public Box, 200 Private User Boxes 100 Folders Per Box, 400 Documents Per Folder/Box, Capacity of Boxes

200 Pages Per Document

GR1320

GR1330

GR1340

KK5008

G01280

KK2560

### **ACCESSORIES (OPTIONS)**

#### **Additional Paper Options**

Large Capacity Feeder - 2,500 Sheet
Large Capacity Feeder - 2,000 Sheet
LCF Connector (to Add 2K LCF)

MP2503L
MP2002L
KN9000 **Finishing Options** 65-Sheet Staple Finisher 65-Sheet Saddle-Stitch Finisher M. I1115 MJ1116 Hole Punch for MJ1115/MJ1116 MJ6108N Exit Tray K6551 Connectivity/Security Options

FAX Unit/2<sup>nd</sup> Line for FAX Unit GD1370N Wireless LAN/Bluetooth GN4030A3 GS1100NODE GR9001 Fax Over IP License Key Bluetooth Keyboard 2<sup>nd</sup> NIC Holder GR1430 USB Hub GR1420 Meta Scan Enabler Security SSD (512GB) GS1010NODE GF1280 FIPS HDD (320GB) GE1260

**Miscellaneous Options** Card Reader Holder Accessory Tray

Panel 10-Key Option Manual Pocket Harness for Coin Controller Accessible Arm

**Software Options** 

e-BRIDGE Global Print GB2550NODE IPSec Fnabler GP1080NODE Unicode Font Enabler GS1007NODE Multi-Station Print Enabler GS1090NODE Per Seat License

e-BRIDGE Plus for OneDrive for Business V3.0 GB2300NODE e-BRIDGE Plus for SharePoint GB2310NODE Online V3.0

e-BRIDGE Plus for Exchange Online V3.0 GB2320NODE Workplace Productivity Bundle e-BRIDGE Plus for Gmail GB2330NODE GB2380NODE e-BRIDGE Plus for Google

Workspace GB2390NODE e-BRIDGE Plus Voice Guidance GB2540NODE















Designs and specifications subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage, letter-size page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. AirPrint® and the AirPrint® logo are trademarks of Apple Inc. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

**Corporate Office** 

**East Coast** 

Midwest

South

**West Coast** 

Website

25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000 959 Route 46 East, 5th Floor, Parsippany, NJ 07054

Tel: 973-316-2700 8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60631

Tel: 773-380-6000 2037 Bakers Mill Rd., Dacula, GA 30019 Tel: 678-546-9385

25530 Commercentre Drive, Lake Forest, CA 92630 Tel: 949-462-6000 business.toshiba.com