

# TOSHIBA

## e-STUDIO™ 1058/1208

- > Departmental/Light Production
- > Advanced Paper Handling
- > Proven Reliability
- > High Volume
- > Solutions Ready



# e-STUDIO™ 1058/1208

## Main Specifications

<b>e-STUDIO1058/1208</b>	Base models include LCD, 250-sheet DSPF, 3,000-sheet paper capacity, 1 TB hard disk drive, PCL6®/Adobe® PostScript® 3™ network printing, color network scanning, web browser, swing out keyboard, application communication module and external accounting module
<b>Type</b>	Console, Monochrome Multi-Function Digital Document System
<b>Display</b>	15.4" (diagonally measured) color dot matrix high-resolution touch panel tilting display. 1280 x 800 dots (WXGA)
<b>Functions</b>	Copy, Print, Network Print, Network Scan and Document Filing <sup>1</sup>
<b>Copy System</b>	Dry Electrostatic Transfer/Dual Component Developer/Magnetic Brush Development/OPC/White LED Exposure/Heat Roller Fusing
<b>Originals</b>	Sheets and Bound Documents
<b>Max Original Size</b>	11" x 17"
<b>Copy Size</b>	Min. 5.5" x 8.5", Max. 11" x 17" + 12" x 18"
<b>Copy Speed</b>	105/120 PPM (8.5" x 11")
<b>Multiple Copy</b>	Max. 9999 Copies
<b>First Copy Time</b>	e-STUDIO1058 e-STUDIO1208
	Platen Glass 3.2 3.2
	DSPF 5.5 5.5
<b>Warm Up Time</b>	210 Seconds <sup>2</sup>
<b>Magnification</b>	25% to 400% in 1% Increments (with Document Feeder 25%-200%)
<b>Original Feed</b>	250-Sheet DSPF
<b>Scan Speed</b>	DSPF Scan: Up to 200 IPM <sup>2</sup> (Monochrome or Color)
<b>Original Sizes</b>	5.5" x 8.5", 8.5" x 11", 8.5" x 11" R, 8.5" x 14", 11" x 17"
<b>Paper Capacity</b>	Std. 3,000 Sheets/Max. 13,500 Sheets
<b>Paper Feed Sizes</b>	Standard: Tandem Tray 1 - 1200 Sheets (Letter), Tandem Tray 2 - 800 Sheets (Letter), Trays 3/4 - 500 Sheets ea. (Letter/Legal/Ledger/Statement/12" x 18"). Optional: Multi-Bypass Tray (for Machine) - 100 Sheets (Letter/Legal/Ledger/Statement/12" x 18"), Multi-Bypass (for LCT) - 500 Sheets (Letter/Legal/Ledger/Statement/12" x 18"), LCT (2-Drawer) - 2,500-Sheets Each Drawer (Letter/Legal/Ledger/12" x 18"), Letter LCC - 3,500 Sheets (Letter)
	Tandem Trays - 16-28 lb Bond, Trays 3/4 - 16 lb Bond to 100 lb Bristol, Multi-Bypass Tray (for Machine) - 15 lb Bond to 110 lb Cover, Multi-Bypass Tray (for LCT) - 15 lb Bond to 100 lb Bristol, LCT (2-drawer) - 15 lb. bond to 110 lb. cover, Letter LCC - 16 lb. bond to 110 cover <sup>2</sup> . Supported paper types include thin, plain, recycled, color, letter head, pre-printed and pre-punched, embossed and glossy.
<b>Paper Weights and Types</b>	
	Standard Automatic Duplex Copying and Printing
<b>Duplexing</b>	Up to 1.8 GHz Multi-Processor Controller
<b>CPU</b>	RJ-45 Ethernet (10/100/1,000 Base-T), USB 2.0 (2 host ports, front and rear), USB 2.0 (1 device port)
<b>Interface</b>	
<b>Memory</b>	Standard 5 GB
<b>Hard Disk Drive</b>	1TB
<b>Resolution Scan/Copy</b>	1200 x 1200 dpi / 600 x 600 dpi
<b>Copy Modes</b>	Monochrome/Grayscale
<b>Exposure Control Modes</b>	Text, Text/Printed-Photo, Printed-Photo, Text Photo, Photo, Map, Pale-Color Settings: Auto or 9 Step Manual 256 Gradations/2 Levels (Monochrome)
<b>Half-tone</b>	Electronic Sort, Auto Paper Selection (APS), Auto Magnification Selection (AMS), Image Preview/Edit, Auto Tray, Paper Type Selection Switching, Rotate Copy, Reserve Copy, Tandem Copy, Book Copy, Margin Shift, Edge/Center Erase, Book Divide, Dual Page, Cover/Insert Page, OHP Insert, Job Build, Card Shot, Blank Page Skip, Mirror/B/W Reverse, Proof, Pamphlet, Watermark, Custom Image, Job Programs
<b>Account Control</b>	Up to 1,000 users. Supports user-number authentication (on device), login name/password or login name/password (via LDAP server) for Copy, Print, Scan and document management.
<b>Output Tray Capacity</b>	Main output tray (top) 250 sheets (face down)
<b>Configuration Method</b>	Web-based management with user/administrator level login, cloning (1 to N) with SRDM and remote front panel access
<b>Service/Functions</b>	Remote front panel, remote access to service logs and click counts
<b>Accessibility</b>	Tilt Front Panel, Adjustment of Key Touch, Document Feeder Free
<b>Features</b>	Stop, Job Programs, Remote Front Panel, Universal Grip for Paper Trays, and Disable Screen Timeout
<b>Environmental</b>	International ENERGY STAR® Program Ver. 2.0, Law on Promoting Green Standards Purchasing, European RoHS (Restriction of Hazardous Substances)
<b>Power Source</b>	AC 208-240 VAC, 60 HZ, 15 Amps Power
<b>Consumption Maximum</b>	3.55 kW or Less
<b>Weight</b>	Approx. 661 lb
<b>Dimensions</b>	Approx. 45" (w) x 30½" (d) x 60¼" (h)

## Network Printing System (Standard)

<b>PDL</b>	PCL6 compatible, True Adobe, PostScript 3, optional XPS
<b>Resolution</b>	1200 x 1200 dpi
<b>Print Speed</b>	105/120 Pages Per Minute (8½" x 11")
<b>Print Drivers</b>	Windows® Server® 2008-2012, Windows Server 2008-2012 x64, Windows 7, Windows 7 x64, Windows 8, Windows 8 x64, Windows 8.1, Windows 8.1 x64, Windows 10, Windows 10 x64, MAC OSX (including 10.4-10.11)
<b>Features</b>	Auto configuration, continuous printing, electronic sorting, N-up printing, duplex printing, transparency inserts, margin shift, image rotation, different cover page, poster print, job bypass print, job retention, confidential print, proof print, user authentication, image stamp and watermarks. Additional features: Multiple pamphlet print, network tandem print, carbon copy print mode, different cover page/last page/other page, form overlay, tab paper settings, tab printing, chapter inserts and page Interleave <sup>1</sup> File Types: TIFF, JPEG, PCL, PRN, TXT, PDF, Encrypted PDF, Compressed PDF/A1, PostScript and Windows XPS1. Methods: FTP, Web page, Email, Network Folder and USB. Methods: FTP, Web Page, Email, Network Folder and USB
<b>Direct Printing</b>	80 Outline Fonts (PCL), 139 Fonts (PS)
<b>Resident Fonts</b>	RJ-45 Ethernet 10/100/1,000 Base-T, USB 2.0
<b>Interface</b>	Windows Server 2008-2012, Windows 7, Windows 8/8.1, Windows 10, MAC OS X (10.4-10.11), Unix®, Linux®, and Citrix® XenApp
<b>Operating Systems</b>	

Designs and specifications are subject to change without notice. Specifications may vary by conditions of use and/or environmental usage. For best results and reliable performance, always use supplies manufactured or designated by Toshiba. Not all options and accessories may be available at the time of product launch. Please contact a local Authorized Toshiba Dealership for availability. Toner yields are estimates based on 5% coverage of a Letter-sized page. Driver and connectivity feature support varies by client/network operating system. Product names may be trademarks of their respective companies. This is a Class 1 laser product complying with IEC60825-1. All company and/or product names are trademarks and/or registered trademarks of their respective manufacturers in their markets and/or countries.

<b>Network Protocols</b>	TCP/IP (IPv4, IPv6, IPSEC) SSL (HTTP, IPP, FTP), SNMPv3, SMTP, POP3, LDAP, 802.1x for Windows and Unix. LPD and LPR for Unix. IPX/SPX® for Novell environments and EtherTalk®, AppleTalk® for Macintosh® environments. <sup>1</sup>
<b>Printing Protocols</b>	LPR, IPP, IPPS, PAP, Raw TCP (port 9100), FTP and Novell Pserver/Rprinter
<b>Network Security</b>	IP/MAC address filtering, protocol filtering, port management, user authentication and document administration. <sup>1</sup>
<b>Security Standards</b>	IEEE-2600TM-2008, DoD (NSTISSP) #11, DoD Directive 8500.2, DoD (DISA)

## Network Scanning System (Standard)

<b>Scan Modes</b>	Standard: Color, monochrome, grayscale
<b>Max. Original Size</b>	11" x 17"
<b>Optical Resolution</b>	600 dpi
<b>Output Modes</b>	600 dpi, 400 dpi, 300 dpi, 200 dpi, 150 dpi, 100 dpi
<b>Image Formats</b>	Monochrome: TIFF, PDF, Encrypted PDF, XPS, PDF/A Color/Grayscale: Color TIFF, JPEG, PDF, Encrypted PDF <sup>1</sup> , PDF/A <sup>1</sup> , Compressed PDF <sup>1</sup> , XPS <sup>1</sup>
<b>Image Compression</b>	Monochrome Scanning: Uncompressed, G3 (MH), G4 (MR/MMR) Color/Grayscale: JPEG (high, middle, low) Up to 2,000 (combined scan destinations)
<b>One-touch Destinations</b>	
<b>Group Destinations</b>	Up to 500
<b>Programs</b>	48 (combined)
<b>Max. Jobs</b>	Up to 100
<b>Network Protocols</b>	TCP/IP and TLS (includes HTTP, SMTP, LDAP, FTP, POP3), SMB, ESMTMP and 802.1x.
<b>Network Security</b>	Email server user authentication for LDAP and Active Directory

## 4K 100-Sheet Stapler/Finisher (MX-FN21: option)

<b>Type</b>	4,000-Sheet Console Stapler Finisher (100-Sheet Stapling)
<b>Output Trays</b>	Upper Tray: Moving Offset Tray (Up to 1,500 Letter Sheets) Middle Tray: 250 Sheets (Letter, Non-Stapled) Lower Tray: Moving Offset Tray (Up to 2,500 Letter Sheets) Up to 100 Sheets (Letter/Statement)
<b>Stapling Capacity</b>	Up to 100 Sheets (Letter/Statement)
<b>Stapling Media</b>	Plain Paper, Letter/Legal/Ledger or Mixed
<b>Stapling Positions</b>	1 Front, 1 Rear, or 2 Point Stitching
<b>Hole Punching</b>	Optional Three-Hole Punch Unit MX-PN13B
<b>Power Source</b>	20 VAC, 60 HZ, 15 Amps
<b>Power Consumption</b>	200W/350W with MX-FD10
<b>Weight</b>	Approx.: 134.5 lb
<b>Dimensions</b>	Approx.: 35.25" (W) x 30" (D) x 41" (H) (with Tray Extended)

## 4K 100-Sheet Stapler/Saddle-Stitch Finisher (MX-FN22: option)

<b>Type</b>	4,000-Sheet Console Stapler Finisher (100-Sheet Stapling)
<b>Output Trays</b>	Upper Tray: Moving Offset Tray (Up to 1,500 Letter Sheets) Middle Tray: 250 Sheets (Letter, Non-Stapled) Lower Tray: Moving Offset Tray (Up to 2,500 Letter Sheets) Up to 100 Sheets (Letter/Statement)
<b>Stapling Capacity</b>	Up to 100 Sheets (Letter/Statement)
<b>Stapling Media</b>	Plain Paper, Letter/Legal/Ledger or Mixed
<b>Stapling Positions</b>	1 Front, 1 Rear, or 2 Point Stitching
<b>Saddle Stitch</b>	Center Stitch/Center Fold (2 Staples) Letter/Legal/Ledger Paper, Saddle-Stitch Up to 5 Sets (16-20 Sheets)/10 Sets (11-15 Sheets)/15 Sets (6-10 Sheets)/Max. Sets: 25 (1-5 Sheets)
<b>Hole Punching</b>	Optional Three-Hole Punch Unit MX-PN13B
<b>Power Source</b>	120 VAC, 60 HZ, 15 Amps
<b>Power Consumption</b>	200W/350W with MX-FD10
<b>Weight</b>	Approx. 134.5 lb
<b>Dimensions</b>	Approx. 35.25" (W) x 30" (D) x 41" (H) (with Tray Extended)

## Optional Equipment

<b>MX-CF11</b>	Insertor
<b>MX-FD10</b>	Multi-Folding Unit
<b>MX-LC12</b>	3,500-Sheet Large Capacity Cassette (Letter)
<b>MX-LC13N</b>	5,000-sheet Large Capacity 2-Drawer Air Feed Tray (Ledger)
<b>MX-MFX1</b>	100-Sheet Multi-Bypass Tray (for Machine)
<b>MX-MF11</b>	500-Sheet Multi-Bypass Tray (for MX-LC13)
<b>MX-FN21</b>	4K Stacking 100-Sheet Staple Finisher
<b>MX-FN22</b>	4K Stacking 100-Sheet Staple/Saddle Stitch Finisher
<b>MX-CF11</b>	2-Tray Insertor Unit
<b>MX-FD10</b>	Multi-Folding Unit
<b>MX-RB16</b>	Large Capacity Tray Mounting Kit
<b>MX-RB17</b>	Large Capacity Tray Tandem Connecting Kit
<b>MX-RB18</b>	Curl Correction Unit
<b>MX-RB13</b>	Relay Unit
<b>MX-TM10</b>	Trimmer Unit
<b>MX-PN13B</b>	3-Hole Punch Unit (for MX-FN21/FN22)
<b>MX-SL10N</b>	Status Indicator

## Supplies

<b>T1207U</b>	Toner Cartridge (Yield 120K @ 5%)
<b>6LS00016000</b>	Developer D1207
<b>Staple2400</b>	Staple Cartridge (for MX-FN22 - Saddle)
<b>Staple2600</b>	Staple Cartridge (for MX-FN21/FN22)

<sup>1</sup> Some features require optional equipment. See your local dealer.

<sup>2</sup> Specification may vary depending on product configuration, machine settings and operating conditions.

## Corporate Office

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## East Coast

959 Route 46 East, 5th Floor, Parsippany, NJ 07054  
Tel: 973-316-2700

## Midwest

8770 W. Bryn Mawr Ave., Suite 700, Chicago, IL 60633  
Tel: 773-380-6000

## South

2037 Bakers Mill Rd., Dacula, GA 30019  
Tel: 678-546-9385

## West Coast

25530 Commercentre Drive, Lake Forest, CA 92630  
Tel: 949-462-6000

## Web Site

www.business.toshiba.com