



imageFORCE
4145/4135/4125

THE POWER OF
NEXT



imageFORCE 4145 with optional accessories.

SPECIFICATIONS

Main Unit

Technology/Type	OLED/A3 Monochrome Multifunction
Core Functions	Standard: Print, Copy, Scan, Send, Store Optional: Fax, Up to 4 lines
Print/Copy Speed (B/W)	imageFORCE 4145: Up to 45 ppm (Letter) Up to 32 ppm (Letter-R) Up to 25 ppm (Legal) Up to 22 ppm (11"x17") imageFORCE 4135: Up to 35 ppm (Letter) Up to 23 ppm (Letter-R) Up to 17 ppm (Legal) Up to 17 ppm (11"x17") imageFORCE 4125: Up to 25 ppm (Letter) Up to 20 ppm (Letter-R) Up to 15 ppm (Legal) Up to 15 ppm (11"x17")
Control Panel	10.1 inch TFT LCD WSVGA Color Touch panel
Memory	RAM 5.0GB
Solid-State Drive	Standard: 256 GB Optional: 1TB
Interface Connections	NETWORK Standard: 1000Base-T/100Base-TX/10Base-T, Optional: Wireless LAN (IEEE 802.11 a/b/g/n/ac/ax) OTHERS Standard: USB 2.0 (Host) x1, USB 3.0 (Host) x1, USB 2.0 (Device) x1 Optional: Serial Interface, Copy Control Interface
Paper Sources (Letter, 20 lb bond)	Standard: Dual 550-sheet Paper Cassettes, 100-sheet Multi-Purpose Tray Optional: 6,350 sheets with High Capacity Cassette Feeding Unit-G1 + Paper Deck Unit-F3

Paper Supply Capacity (Letter, 20 lb. Bond)	Standard: 1,200 sheets Maximum: 6,350 sheets
Output Options	1st Copy Tray Kit-C1, Inner 2way Tray-M1 ¹ , Copy Tray-T2, Inner Finisher-N1, Staple Finisher-AH1, Staple Finisher Lite-B1, Booklet Finisher-AH1, Inner 2/3 Hole Puncher-D1 ² , 2/3 Hole Puncher Unit-A1 ³
Output Capacity (Letter, 20 lb. Bond)	Standard: 250 Sheets Maximum: 3,450 Sheets
Finishing Capabilities	Collate, Group, Offset, Staple, Saddle Stitch, Hole Punch, Eco Staple, Staple On Demand (Capabilities vary depending on the options installed)
Supported Media Types	Upper Cassette: Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope ⁴ Lower Cassette: Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead, Envelope ⁵ Multi-purpose tray: Thin, Plain, Recycled, Color, Heavy, Coated, Tracing, Bond, Transparency, Labels, Pre-punched, Letterhead, Envelope

SPECIFICATIONS CONTINUED

imageFORCE 4145/4135/4125

Supported Media Sizes	Upper Cassette: Standard size: Letter, Executive, Statement-R Custom Size: 4-1/8" x 5-7/8" to 11-3/4" x 8-1/2" Envelopes: ISO-C5
	Lower Cassette: Standard size: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement-R Custom Size: 4-1/8" x 5-7/8" to 12" x 18" Envelopes: COM10 No.10, Monarch, DL
	Multi-purpose tray: Standard size: 12"x18", 11"x17", Legal, Letter, Letter-R, Executive, Statement, Statement-R, Custom size: 3-7/8" x 5-1/2" to 12-5/8" x 18" Free size: 4" x 5-7/8" to 12" x 18" Long sheet: 3-7/8" x 18" to 12-5/8" x 47-1/4" Envelopes: COM10 No.10, Monarch, ISO-C5, DL Envelope custom size: 3-7/8" x 3-7/8" to 12-5/8" x 18"
Supported Media Weights	Upper Cassette: 14 lb. bond to 140 lb. index (52 to 256 gsm)
	Lower Cassette: 14 lb. bond to 140 lb. index (52 to 256 gsm)
	Multi-purpose tray: 14 lb. bond to 110 lb. cover (52 to 300 gsm)
Warm-up Time	Duplexing: 14 lb. bond to 80 lb. cover (52 to 220 gsm)
	Quick Startup Mode: 4 seconds or less ⁷
	From Sleep Mode: 10 seconds or less
Dimensions (W x D x H)	From Power On: 10 seconds or less ⁸
	With Platen Cover-Y3: 22-1/4" x 29-3/8" x 31" (565 x 745 x 788 mm)
	With Single Pass DADF-E1: 22-1/4" x 29-3/8" x 35-3/8" (565 x 745 x 897 mm)
Installation Space (W x D)	With Single Pass DADF-F1: 22-1/4" x 29-3/8" x 34" (565 x 745 x 862 mm)
	Basic: 38-1/2" x 45-3/8" (978 x 1,152 mm) (Right Door & Multi-Purpose Tray Opened + Paper Cassette Opened)
	Fully Configured: 65" x 45-3/8" (1,651 x 1,152 mm) (with Single Pass DADF-E1/F1 + Staple Finisher-AH1/ Booklet Finisher-AH1 + Copy Tray-T2 Extended + Paper Cassette Open)
Weight	With Platen Cover-Y3: Approx. 143.3 lb. (65 kg) ⁹
	With Single Pass DADF-E1: Approx. 174.2 lb. (79 kg) ⁹
	With Single Pass DADF-F1: Approx. 157.0 lb. (72 kg) ⁹
Print Specifications	
Print Resolution (dpi)	Up to 4800 dpi x 2400 dpi ¹⁰
Standard Page Description Languages	Standard: UFR II, PCL6/PCL5, Adobe® PostScript®3™
Direct Print Supported File Types	PDF, EPS ¹¹ , TIFF/JPEG, XPS
Printing from Mobile and Cloud	AirPrint, Mopria, IPP Everywhere, Canon PRINT, uniFLOW Online, Universal Print and Cloud Connector
	A range of software and MEAP-based solutions are available to provide printing from mobile devices or internet-connected devices and cloud-based services ¹² depending on your requirements. Please contact your sales representative for further information.
Operating System Standard Printing	Android, Windows® 11, Chrome OS, macOS (11.2.2 or later), iOS (15.2 or later), iPadOS
Fonts	PCL fonts: 93 Roman, 10 Bitmap fonts, 2 OCR fonts, Andalé Mono WT J/K/S/T ¹³ (Japanese, Korean, Simplified and Traditional Chinese), Barcode fonts ¹⁴ PS fonts: 136 Roman

Operating System¹⁵	UFR II: Windows® 11/Server2016/Server2019/Server2022/Server2025, macOS (11.7 or later) PCL: Windows® 11/Server2016/Server2019/Server2022/Server2025 PS: Windows® 11/Server2016/Server2019/Server2022/Server2025, macOS (11.7 or later) PPD: Windows® 11, macOS (11.7 or later)
Copy Specifications	
First-Copy-Out Time (Letter, BW)	imageFORCE 4145: As fast as 4.6 seconds
	imageFORCE 4135: As fast as 5.5 seconds
	imageFORCE 4125: As fast as 6.1 seconds
Copy resolution (dpi)	600 x 600
Multiple Copies	Up to 9,999 copies
Magnification	Variable Zoom: 25% to 400% (1% Increments)
Scan Specifications	
Type	Standard: Color Platen Optional: Platen Cover-Y3, Single Pass Duplexing Automatic Document Feeder (DADF)-E1 or Single Pass DADF-F1 [2-sided to 2-sided (Automatic with Duplexing Automatic Document Feeder)] (Multi-Sheet Feed Detection is supported)
Document Feeder Paper Capacity	Single Pass DADF-E1: up to 200 Sheets (20 lb. Bond) Single Pass DADF-F1: up to 100 Sheets (20 lb. Bond)
Document Feeder Supported Media Sizes	Single Pass DADF-E1: 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R Custom size: 2-3/4" x 5-1/2" to 12" x 17" Single Pass DADF-F1: 11" x 17", Legal, Letter, Letter-R, Statement, Statement-R Custom size: 1-7/8" x 3-3/8" to 12" x 17"
Document Feeder Supported Media Weights	Document Feeder media weight: Single Pass DADF-E1: 1-sided scanning: 13 lb. bond to 80 lb. cover (50 to 220 gsm) 2-sided scanning: 13 lb. bond to 80 lb. cover (50 to 220 gsm) Single Pass DADF-F1: 1-sided scanning: 13 lb. bond to 34 lb. bond (50 to 128 gsm) 2-sided scanning: 13 lb. bond to 34 lb. bond (50 to 128 gsm)
Platen Scanning Size	Up to 11-3/4" x 17"
Pull Scan Specifications	Color Network ScanGear2. For both TWAIN and WIA. Supported OS: Windows® 11/Server 2016/Server 2019/Server 2022/Server 2025
Scan Resolution (dpi)	600 x 600
Scan Method	Push Scan, Pull Scan, Scan to Box, Scan to Advanced Box, Scan to Network, Scan to USB Memory Key, Scan to Mobile devices, Scan to cloud (uniFLOW Online)
Scan Speed (ipm: Letter)	Single Pass DADF-E1: Single-Scanning: 135/135 (300 x 300 dpi, send), 80/80 (600 x 600 dpi, Copy) Double-Sided Scanning: 270/270 (300 x 300 dpi, Send), 160/160 (600 x 600 dpi, Copy)
	Single Pass DADF-F1: Single-Scanning: 80/80 (300 x 300 dpi, Send), 60/- (600 x 600 dpi, Copy) Double-Sided Scanning: 120/120 (300 x 300 dpi, Send), 60/- (600 x 600 dpi, Copy)
Send Specifications	
Destination	Standard: E-mail/Internet FAX (SMTP ¹⁶), SMB, FTP, SFTP, WebDAV, Mail Box Optional: Super G3 FAX, IP Fax
Address Book	LDAP (2,000)/Local (1,600)/Speed dial (200)
Communication Protocol	File: FTP (TCP/IP), SFTP (TCP/IP), SMB3.1.1 (TCP/IP), WebDAV E-mail/iFax: SMTP, POP3

SPECIFICATIONS CONTINUED

imageFORCE

4145/4135/4125

File Format	TIFF (MMR), JPEG ¹⁷ , PDF (Compact, Searchable, Optimize for Web, PDF/A-1b, PDF/A-1a, PDF/A-2a, PDF/A-2b, PDF/A-2u, PDF/A-3a, PDF/A-3b, PDF/A-3u, Trace & Smooth, Encrypted, Device Signature, User Signature), XPS (Compact, Device Signature, User Signature), Office Open XML (PowerPoint, Word)
Send Features	Original Type Selection, Two-sided Original, Book to Two Pages, Different-size Originals, Density Adjustment, Sharpness, Erase Frame, Job Build, Delayed Send, Preview, Job Done Notice, File Name, Subject/Message, Reply-to, E-mail Priority, TX Report, Original Content Orientation, Skip Blank Originals, Dropout Color
Fax Specifications	
Modem Speed	Super G3: 33.6 kbps G3: 14.4 kbps
Compression Method	MH, MR, MMR, JBIG
Resolution (dpi)	400 x 400 (Ultra Fine), 200 x 400 (Super Fine), 200 x 200 (Fine), 200 x 100 (Normal)
Sending/Receiving Size	11"x17", Legal, Letter, Letter-R, Statement-R
FAX Memory	Up to 30,000 pages (2,000 Jobs)
Speed Dials	Max. 200
Group Dials/Destinations	Max. 199 dials
Sequential Broadcast	Max. 256 Addresses
Memory Backup	Yes
Store Specifications	
Mail Box (Number Supported)	100 User Inboxes, 1 Memory RX Inbox, 50 Confidential Fax Inboxes Maximum 30,000 Pages (2,000 jobs) Stored
Advanced Box	Communication Protocol: SMB or WebDAV Supported Client PC: Windows® 11 ¹⁸ Concurrent Connections (Max.): SMB:64, WebDAV:3
Advanced Box Available Disc Space	Approx. 16 GB (Standard SSD) Approx. 480 GB (With Optional 1 TB SSD)
Security Specifications	
Authentication and Access Control	User Authentication (Picture Login, Picture and PIN Login, Card Login, Username and Password Login, Function Level Login, Mobile Login), Department ID Authentication (Department ID and PIN Login, Function Level Login), uniFLOW Online/uniFLOW ¹⁹ (PIN Login, Picture Login, Picture and PIN Login, Card Login, Card and PIN Login, Username and Password Login, Department ID and PIN Login, Function Level Login), Microsoft Entra ID Authentication (Password Login, Card Login), Google Workspace (Password Login, Card Login), Two-Factor Authentication at LUI/RUI, Access Management System (Access Control)
Document Security	Print Security (Secure Print, Encrypted Secure Print, Forced Hold Printing, uniFLOW Secure Print ¹⁹), Receive Data Security (Confidential Fax Inbox Forwarding Received Documents Automatically), Scan Security (Encrypted PDF, Device Signature PDF/XPS, User Signature PDF/XPS), BOX Security (Mail Box Password Protected, Advanced Box Access Control), Send Data Security (Setting for requesting password input per transmission, Restricted E-mail/File send functions, Confirming FAX number, Allow/Restrict Fax Driver Transmissions, Allow/Restrict Sending from History, S/MIME Support), Secure Watermark

Network Security	TLS 1.3 (FIPS140-3), IPSec (FIPS140-3), IEEE802.1X authentication, SNMPv3, Firewall Functionality (IP/MAC Address Filtering), Dual Network Support (Wired LAN/Wireless LAN, Wired LAN/Wired LAN), WPA3 support (Wi-Fi), Enabling/Disabling (Network Applications, Remote UI, USB Interface), G3 FAX separation from LAN, USB Port separation from LAN, Prohibit the execution of files stored in Advanced Box in the MFP, Scan and Send -Virus Concerns for E-mail Reception
Device Security	Protecting SSD Data [SSD Data Encryption (FIPS140-3), SSD Lock], Standard SSD Initialize, Initialize (NIST 800-88 PURGE LEVEL), Trusted Platform Module (TPM 2.0), Job Log Conceal Function, Protecting MFP Software Integrity: Verify System at Startup (NIST SP800-193: Protection), Checking MFP Software Integrity & Platform Firmware Resiliency: Automatic System Recovery (NIST SP800-193: Recovery), Runtime Intrusion Detection: Trellix Embedded Control ²⁰ , HCD-PP Common Criteria Certification (Validation pending)
Device Management and Auditing	Administrator Password, Digital Certificate and Key Management, SAN certificates, Audit Log, Cooperating with External Security Audit System (SIEM: Security Information and Event Management) ²¹ , Image Data Logging, Security Policy Setting
Environmental Specifications	
Operating Environment	Temperature: 50 to 86 °F Humidity: 20 to 80 % RH (Relative Humidity)
Power Source	120-127 V 60 Hz 8.5A
Power Consumption	Maximum: Approx. 1,500 W Sleep Mode: Approx. 0.5 W ²² Typical Electricity Consumption (TEC) ²³ imageFORCE 4145 : 0.43 kWh imageFORCE 4135 : 0.31 kWh imageFORCE 4125 : 0.21 kWh
Environmental Standards	ENERGY STAR® Certified EPEAT Gold
Consumables	
Toner Cartridges	GPR-1010 Toner Bk
Toner Yield (Estimated @ 6% Coverage)	GPR-1010 Toner Bk: Approx. 42,000 pages
Paper Source Options	
Cassette Feeding Unit-BB1	Paper Capacity: Dual 550-Sheet Paper Cassettes (20 lb bond) Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Transparency, Pre-punched, Letterhead Paper Size: 12"x18", 11"x17", Legal, Letter, Letter-R, Executive, Statement-R Custom Size: 4-1/8" x 5-7/8" to 12" x 18" Paper Weight: 14 lb bond to 140 lb index (52 to 256 gsm)
High Capacity Cassette Feeding Unit-G1	Paper Capacity: Up to 2,450 sheets [20 lb bond (75 gsm)] Paper Type: Thin, Plain, Recycled, Color, Heavy, Bond, Pre-punched, Letterhead Paper Size: Letter Paper Weight: 14 lb. bond to 140 lb. index (52 to 256 gsm)
Paper Deck Unit-F3	Paper Capacity: Up to 2,700 Sheets Paper Type: Thin, Plain, Recycled, Color, Pre-punched Paper Size: Letter Paper Weight: 14 lb. bond to 28 lb. bond (52 to 105 gsm)

SPECIFICATIONS CONTINUED

imageFORCE 4145/4135/4125

Paper Output Options ²⁴	
1st Copy Tray Kit-C1	Tray Capacity: Letter, Statement, Statement-R: Up to 250 sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 100 sheets Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm)
Inner 2way Tray-M1	(Requires 1st Copy Tray Kit-C1) Tray Capacity: Letter, Statement, Statement-R: Up to 100 sheets 12" x 18", 11" x 17", Legal, Letter-R, Executive: Up to 50 sheets Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm)
Copy Tray Kit-T2	Tray Capacity: Letter, Statement-R: Up to 100 sheets 11" x 17", Legal, Letter-R, Executive: Up to 75 sheets Paper Weight: 14 lb bond to 80 lb cover (52 to 220 gsm)
Inner Finisher-N1	Tray Capacity [with 20 lb bond (75 gsm)]: Upper Tray: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R: Up to 50 sheets Long sheet length of up to 35-1/2": 1 sheet Lower Tray: Letter, Executive, Statement, Statement-R: Up to 500 sheets, 11" x 17", Legal, Letter-R: Up to 250 sheets 12" x 18", Envelope: Up to 10 sheets Paper Weight: 14 lb bond to 110 lb cover (52 to 300 gsm) Staple Position: Corner, Double Staple Capacity: [14 to 24 lb bond (52 to 90 gsm)] Letter, Executive: Up to 50 sheets Letter-R: Up to 40 sheets 11" x 17", Legal: Up to 30 sheets Eco Staple: 11" x 17", Letter: Up to 10 Sheets [14 lb bond to 17 lb bond (52 to 64 gsm)] Up to 8 sheets [18 lb bond to 21 lb bond (65 to 81.4 gsm)] Up to 6 sheets [22 lb bond to 28 lb bond (82 to 105 gsm)] Staple On Demand: Up to 40 sheets [20 lb bond (75 gsm)]
Staple Finisher-AH1	Tray Capacity [with 20 lb bond (75 gsm) paper]: Upper Tray: Letter, Executive, Statement, Statement-R: Up to 250 sheets 12" x 18", 11" x 17", Legal, Letter-R: Up to 125 sheets Lower Tray: Letter, Executive, Statement, Statement-R: Up to 3,000 sheets 12" x 18", 11" x 17", Legal, Letter-R: Up to 1,500 sheets Envelope: Monarch: Up to 30 sheets, COM10 No.10/DL ISO-C5: Up to 100 sheets Long sheet length of up to 47-1/4": 1 sheet (ejected to the top of the buffer pass unit and the finisher) Paper Weight: Upper Tray: 14 lb bond to 140 lb index (52 to 256 gsm) Lower Tray: 14 lb bond to 110 lb cover (52 to 300 gsm) Staple Position: Corner, Double Staple Capacity: [14 lb bond to 24 lb bond (52 to 90 gsm)] Letter, Executive: Up to 50 sheets Letter-R: Up to 40 sheets 11" x 17", Legal: Up to 30 sheets Eco Staple: 11"x17", Letter: Up to 10 Sheets [14 to 17 lb bond (52 to 64 gsm)] Up to 8 Sheets [18 to 21 lb bond (65 to 81.4 gsm)] Up to 6 Sheets [22 to 28 lb bond (82 to 105 gsm)] Staple On Demand: Up to 50 sheets [20 lb bond (75 gsm) paper]

Staple Finisher Lite-B1	Tray Capacity [with 20 lb bond (75 gsm)]: Upper Tray: Letter, Executive, Statement, Statement-R: approx. 250 sheets 12" x 18", 11" x 17", Legal, Letter-R: approx. 125 sheets Lower Tray: 12" x 18", 11" x 17", Legal, Letter, Letter-R, Executive, Statement, Statement-R: 1,500 sheets Envelopes: Monarch: 30 sheets, COM10 No.10, DL, ISO-C5: 100 sheets Long sheet length of up to 47-1/4": 1 sheet (ejected to the top of the buffer pass unit and the finisher) Paper Weight: Upper Tray: 14 lb bond to 140 lb index (52 to 256 gsm) Lower Tray: 14 lb bond to 110 lb cover (52 to 300 gsm) Staple Position: Corner, Double Staple Capacity: [14 to 24 lb bond (52 to 90 gsm)] Letter, Executive: 50 sheets Letter-R: 40 sheets 11" x 17", Legal: 30 sheets Staple On Demand: 50 sheets [14 lb bond to 24 lb bond (52 to 90 gsm)]
Booklet Finisher-AH1	(Includes the above Staple Finisher-AH1 basic staple specifications.) Saddle Stitch Paper Size: 12" x 18", 11" x 17", Legal, Letter-R Saddle Stitch Staple Capacity: 20 sheets x 10 sets [14 lb bond to 21 lb bond (52 to 81.4 gsm)] [including 1 cover sheet up to 140 lb index (256 gsm)] Non Staple Folded Bunch Capacity: up to 3 sheets [14 lb bond to 28 lb bond (52 to 105 gsm)]
Inner 2/3 Hole Puncher-D1	(Requires Inner Finisher-N1) Two or Three Holes Acceptable Punch Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm) Acceptable Punch Paper Size: Two holes: 11"x17", Legal, Letter, Letter-R, Executive Three holes: 11"x17", Letter, Executive
2/3 Hole Puncher Unit-A1	(Requires either the Staple Finisher-AH1, Staple Finisher Lite-B1, or Booklet Finisher-AH1) Two or Three Holes Acceptable Punch Paper Weight: 14 lb. bond to 110 lb. cover (52 to 300 gsm) Acceptable Punch Paper Size: Two holes: 11" x 17", Legal, Letter, Letter-R, Executive Three holes: 11" x 17", Letter, Executive

- ¹ Requires 1st Copy Tray Kit-C1.
- ² Requires the Inner Finisher-N1.
- ³ Requires either the Staple Finisher-AH1 or Booklet Finisher-AH1.
- ⁴ Envelope Feeder Attachment B (standard) is required except ISO-C5.
- ⁵ Envelope Feeder Attachment A (standard) is required.
- ⁶ Long Sheet Feeding Tray-A1 is required.
- ⁷ Time from device power-on to when the copy icon appears and is enabled to operate on the touch panel display.
- ⁸ Time from device power-on until copy ready (not print reservation).
- ⁹ Including the optional 1st Copy Tray Kit-C1 and includes consumables.
- ¹⁰ Data processing is 4,800 equivalent x 2,400 equivalent.
- ¹¹ EPS can be printed directly only from the Remote User Interface.
- ¹² Subscription to a third-party cloud service required. Subject to third-party cloud service provider's Terms and Conditions.
- ¹³ Optional PCL International Font Set-A1 is required.
- ¹⁴ Optional Barcode Printing Kit-D1 is required.
- ¹⁵ Other operating systems and environments, including AS/400, UNIX, Linux, and Citrix may be supported. Some of these solutions are chargeable. SAP Device Types are available via the SAP Market Place. For more information, contact your sales representative.
- ¹⁶ Available OAuth 2.0 authentication method on Microsoft Exchange Online and Google Workspace.
- ¹⁷ Single-Page only.
- ¹⁸ Windows 11 only supports SMB.
- ¹⁹ Requires optional uniFLOW Online/uniFLOW.
- ²⁰ This feature is off by default and must be turned on by the user. Warm-up times are affected once turned on. Note: See Product Specifications Sheet for a complete list of standard and optional security features.
- ²¹ Third-party SIEM system required. Subject to third-party SIEM system's Terms and Conditions. Canon cannot ensure compatibility with all third-party SIEM systems.
- ²² 0.5 W is not available in all circumstances due to certain settings.
- ²³ Based on ENERGY STAR Product Specification for Imaging Equipment Version 3.2.
- ²⁴ Paper capacity may vary with different paper type/size.



usa.canon.com/business

As an ENERGY STAR® Partner, Canon U.S.A., Inc. has certified this model as meeting the ENERGY STAR® energy efficiency criteria through an EPA recognized certification body. ENERGY STAR® and the ENERGY STAR® mark are registered U.S. marks. Canon, imageFORCE and the GENUINE logo are registered trademarks or trademarks of Canon Inc. in the United States and may also be registered trademarks or trademarks in other countries. Canon products offer certain security features, yet many variables can impact the security of your devices and data. Canon does not warrant that use of its features will prevent security issues. Some security features may impact functionality/performance; you may want to test these settings in your environment. Nothing herein should be construed as legal or regulatory advice concerning applicable laws; customers must have their own qualified counsel determine the feasibility of a solution as it relates to regulatory and statutory compliance. Trellix and the Trellix logo are trademarks or registered trademarks of Musarubra US LLC or its subsidiaries in the U.S. and other countries. All other referenced product names and marks are trademarks of their respective owners. All printer output images are simulated. All features presented in this brochure may not apply to all Series and/or products and may be optional; please check with your Canon Authorized Representative for details. Products shown with optional accessories. Subscription to a third-party cloud service required. Subject to third-party cloud service providers terms and conditions. uniFLOW is a registered trademark of NT-ware Systemprogrammierung GmbH. Canon U.S.A. does not provide legal counsel or regulatory compliance consultancy, including without limitation, Sarbanes-Oxley, HIPAA, GLBA, Check 21, or the USA Patriot Act. Each customer must have its own qualified counsel determine the advisability of a particular solution as it relates to regulatory and statutory compliance. Specifications and availability subject to change without notice. Not responsible for typographical errors.

©2026 Canon U.S.A., Inc. All rights reserved.